

SPIN-VALVE EFFECT IN A Ni-C₆₀-Ni DEVICE

Haiying He and Ravindra Pandey*

Department of Physics and Multi-scale Technology Institute,
Michigan Technological University, Houghton, MI 49931

Shashi P. Karna

US Army Research Laboratory, Weapons and Materials Research Directorate,
ATTN: AMSRD-ARL-WM, Aberdeen Proving Ground, MD 21005-5069

ABSTRACT

We present here the results of theoretical calculations on the spin-valve effect in a Ni-C₆₀-Ni device. The magnitude of the junction magnetoresistance (JMR) is found to be significantly large for the device, which makes it a promising candidate for realistic applications in molecular spintronics. The exploration of the origin of the observed spin-valve effect in the Ni-C₆₀-Ni system will be discussed.

1. INTRODUCTION

Spintronic devices are attractive for many potential Army applications ranging from memory storage and magnetic field sensors to quantum computing devices. The central theme of spintronics is to actively control and manipulate spin degrees of freedom in solid state systems. The prototypical structure of a spin valve consists of two magnetic layers bridged by a non-magnetic spacer: F1/N/F2. In such a device, the conduction electrons experience a lower resistance (R) when the relative orientation of the magnetizations in two ferromagnetic layers F1 and F2 are aligned in parallel (PL, *on* state) than in anti-parallel (AP, *off* state). This is the so-called spin-valve effect or magnetoresistive effect. It is characterized by $JMR=(R_{AP}-R_{PL})/R_{PL}$ in a junction.

The discovery of giant magnetoresistive effect ($MR>10\%$) has led to the present generation of read/write heads for magnetic data storage impacting on a multibillion industry. However, in order to achieve the industrial target of one Tb/in², a further device miniaturization is required, with the ultimate goal of producing atomic scale ultrasensitive sensors used as the magnetic read/write heads. In this line of inquiry, spintronics starts to converge with the burgeoning field of molecular electronics, in the sense that we are now beginning to consider the use of individual molecules as the non-magnetic spacer in a spin valve. The advantages are that the size of molecules is usually in the sub-nanoscale; identical molecules can be manufactured cheaply and easily in industry quantities, and can provide reliable and uniform performance.

To this day, however, only very few rigorous studies have been done in this field (Zwolak *et al.*, 2002; Pati *et al.*, 2003; Wei *et al.*, 2004; Rocha *et al.*, 2005; He *et al.*, 2006), and as a result, many open questions remain. Especially the role of the molecule and the effect of the molecule-electrode interface need to be fully understood before one can develop molecular spintronic devices for specific applications. In this paper, we will discuss results from our first-principles calculations on the spin-polarized electron transport in a two-terminal Ni-C₆₀-Ni device where the fullerene molecule is bonded by atomic-scale ferromagnetic nickel contacts (Fig. 1). There are several advantages of choosing C₆₀ as the spacer. Firstly, the mass-production of C₆₀ is well established. Secondly, C₆₀ is structurally very stable. Last but not least, it is well known that the C₆₀ molecule can be electronically active as either an electron acceptor or an electron donor with a band gap as small as 1.7 eV.




Fig. 1 A schematic illustration of a Ni-C₆₀-Ni molecular device. Top: The left/ right contact region is modeled by a Ni atom and the rest of the semi-infinite electrode is a Ni bulk reservoir, described theoretically by an effective self-energy Σ . Bottom: A slice of the charge density plots of the center scattering region is shown for the bridge site over a C=C double bond (B66).

2. COMPUTATIONAL DETAILS

We begin with the construction of a two-terminal molecular electronic device by coupling the C₆₀ molecule to the ferromagnetic Ni electrodes. Our main interest in

| Report Documentation Page | | | | Form Approved OMB No. 0704-0188 | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|-------------------------------------|-----------------------------------------|------------------------------------------|---------------------------------|
| Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. | | | | | |
| 1. REPORT DATE 01 NOV 2006 | | 2. REPORT TYPE N/A | | 3. DATES COVERED - | |
| 4. TITLE AND SUBTITLE Spin-Valve Effect In A Ni-C60-Ni Device | | | | 5a. CONTRACT NUMBER | |
| | | | | 5b. GRANT NUMBER | |
| | | | | 5c. PROGRAM ELEMENT NUMBER | |
| 6. AUTHOR(S) | | | | 5d. PROJECT NUMBER | |
| | | | | 5e. TASK NUMBER | |
| | | | | 5f. WORK UNIT NUMBER | |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Department of Physics and Multi-scale Technology Institute, Michigan Technological University, Houghton, MI 49931 | | | | 8. PERFORMING ORGANIZATION REPORT NUMBER | |
| 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) | | | | 10. SPONSOR/MONITOR'S ACRONYM(S) | |
| | | | | 11. SPONSOR/MONITOR'S REPORT NUMBER(S) | |
| 12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited | | | | | |
| 13. SUPPLEMENTARY NOTES See also ADM002075., The original document contains color images. | | | | | |
| 14. ABSTRACT | | | | | |
| 15. SUBJECT TERMS | | | | | |
| 16. SECURITY CLASSIFICATION OF: | | | 17. LIMITATION OF ABSTRACT UU | 18. NUMBER OF PAGES 4 | 19a. NAME OF RESPONSIBLE PERSON |
| a. REPORT unclassified | b. ABSTRACT unclassified | c. THIS PAGE unclassified | | | |

the present study lies in understanding of the electronic and transport properties of Ni-C₆₀-Ni for the cases of the parallel (PL) and anti-parallel (AP) spin configurations of the system.

The spin-polarized electronic transport calculations have been performed for Ni-C₆₀-Ni using density functional theory (DFT) (Frisch *et al.*, 1998) in conjunction with the Green's function-based Landauer-Büttiker multi-channel formalism (Landauer, 1989; Büttiker, 1986; Datta, 1995). In such a molecular junction, the metal-molecule interface is expected to play a critical role in determining the current-voltage (*I-V*) characteristics. To investigate the role of the metal-molecule interface, the chemical bonding and its contribution to transmission function will be discussed in detail with respect to the binding sites of Ni on C₆₀.

The Green's function-based Landauer-Büttiker formalism (employing the coherent scattering together with the no spin-flip scattering assumptions) was used to calculate the electron transport properties in a low bias regime for both PL and AP spin configurations of the system. The Ni atom at each side of C₆₀ is assumed to be at the end of a contact which is connected to a Ni electrode reservoir. Since Ni bulk is a ferromagnetic material having unbalanced spin-up (↑) and spin-down (↓) electrons near its Fermi level, the tunneling channels for spin-up (↑) and spin-down (↓) electrons are explicitly separated.

The total current in such a system can be obtained by a summation of the contributions from both the spin-up (I^\uparrow) and the spin-down (I^\downarrow) electrons. The current-voltage (*I-V*) relation is evaluated as follows:

$$I^{\uparrow(\downarrow)} = \frac{2e}{h} \int_{-\infty}^{\infty} dE T^{\uparrow(\downarrow)}(E, V) [f(E - \mu_1) - f(E - \mu_2)] \quad (1)$$

where μ_1 and μ_2 are the electrochemical potentials in the two contacts under an external bias V , $f(E)$ is the Fermi-Dirac distribution function. $T(E, V)$ is the electron transmission function which can be calculated from a knowledge of the molecular energy levels and their coupling to the metallic contacts. $T(E, V)$ is an important intrinsic factor in transport properties, which describes the quantum mechanical transmission probabilities for electrons with energy E under a bias V . As reported in other molecular systems, no significant shift in molecular spectra has been seen in the presence of low applied bias (Heurich *et al.*, 2002; Pati *et al.*, 2003), suggesting one does not expect a significant change in transmission function in the low bias regime that we have considered here either. We have not included the bias induced effect in this study.

3. RESULTS AND DISCUSSION

C₆₀ has a high symmetry of icosahedra I_h consisting of *twelve* regular pentagons and *twenty* regular hexagons. All the C atoms are equivalent with sp^2 hybridization and each C atom is bonded to another three C atoms with two single bonds and one double bond. The C₆₀ molecule offers a variety of sites for atoms bonded to the C₆₀ cage externally. We have performed first principle calculations based on the Dmol program package (Delley, 1990, 2000) to find the site-preference of a Ni atom bonded externally to C₆₀. The B66 site (i.e. the bridge site over a C=C double bond) is found to be the most favorable site for Ni, relative to the B56 site (i.e. the bridge site over a C-C single bond), the H5 site (i.e. the hole site above the center of a pentagonal ring of C atoms), and the H6 site (i.e. the hole site above the center of a hexagonal ring of C atoms). This is consistent with an earlier study reported by Alemany *et al.* (Alemany *et al.*, 2001) using the quenching MD simulation approach.




Fig. 2 The current-voltage (*I-V*) curves for parallel (PL) and anti-parallel (AP) spin configurations of Ni-C₆₀-Ni with Ni binding at the bridge site over a C=C double of C₆₀-B66.

The current-voltage (*I-V*) characteristics have been calculated for both PL and AP spin configurations with Ni binding at the B66 site of C₆₀, as shown in Fig. 2. A significant spin valve effect – higher PL current than AP current, is observed in this system. Moreover, our electronic structure calculations reveal that the ground state (the lowest in energy) of such a system has an anti-parallel spin configuration (*off* state). The natural anti-parallel spin alignment eliminates the need for applying a local magnetic field to obtain an *off* state, which would be a formidable task in a real-world application otherwise. The *I-V* curves are then used to calculate the junction magnetoresistance (JMR) with respect the external bias voltage (Fig. 3). And it shows a relatively small variation

with bias. The magnitude of JMR is found to be significantly large for the device, with a value around 110%. It is close to the maximum experimental value of 80% reported by Ralph's group in Cornell (Pasupathy *et al.*, 2004).




Fig. 3 The junction magnetoresistance (JMR) of Ni-C₆₀-Ni with Ni binding at the B66 site of C₆₀.




Fig. 4. Transmission functions for (a) parallel (PL) (solid line) and (b) anti-parallel (AP) (dashed line) spin configurations of Ni-C₆₀-Ni with Ni binding at the B66 site of C₆₀.

In order to trace the physical origin of this spin-valve effect in C₆₀ mediated spin-polarized electron transport between two ferromagnetic electrodes, we have plotted the transmission functions (T) for the Ni-C₆₀-Ni system in Fig. 5 (a) and (b) for both PL and AP spin configurations. The Ni atom is taken to be bonded externally at the B66 site of the C₆₀ molecule. We note here the similarity in the shape of T except a small shift to lower energy for the AP case relative to the case of PL. It suggests that T

reflects the intrinsic characteristics of the molecule despite the differences intrigued by the different spin configurations. However, a bump appears in the near Fermi region (~ -4 eV) in the case of PL spin configuration, which contributes to a larger current. The feature of this broad peak is currently under investigation.

It is probably due to the interaction between the molecule and electrodes and can often be attributed to the bonding states. The occurrence of this peak (the one instantly below -4 eV) is clearly seen in the α (spin-up) state molecular spectra in the PL configuration. It is the α -HOMO of the extended Ni-C₆₀-Ni molecule complex, which makes the sole contribution to the electron transmission near E_f . Nonetheless, this feature is not found in either the spin-down (β) states in PL configuration or the spin-up and spin-down (α and β) states in AP configuration, where the states below LUMO are only composed of metallic states from the Ni contact.

As a result of this, the tunneling current (obtained through Equation (1)) is significantly higher in the PL case than those in the AP case for both binding sites, which is clearly shown in Fig. 2. In the low bias region (< 0.5 V), a linear response is observed for the PL spin configuration, showing an ohmic-like behavior. However, a closer look at the differential conductance (not shown here) suggests a slightly different trend in the variation of conductance with respect to external bias voltage due to the different variation of transmission function in the vicinity region of E_f .

In the AP case, a linear response in I - V curve in the low bias regime is well preserved. However, the differential conductance dI/dV is significantly decreased compared to the PL alignment of spins between the two contacts.

4. CONCLUSIONS

In summary, density functional theory together with the Landauer-Bütticker formalism is used to calculate the spin-polarized electron transport through a C₆₀ molecule coupled to ferromagnetic Ni electrodes. The tunneling current is found to be highly polarized. A significant spin-valve effect is observed with a JMR of 110%, which is also observed in experiments among the few experimental reports on the spin-valve effect in magnetic-organic systems (Xiong *et al.*, 2004; Petta *et al.*, 2004; Pasupathy *et al.*, 2004). The difference in the transmission function for parallel (PL) and anti-parallel (AP) spin configuration is clearly revealed. A further study of the chemical bonding at the interface of Ni-C₆₀-Ni may shed light on the physical origin of the spin-valve effect.

ACKNOWLEDGMENTS

The research reported in this document was performed in connection with contract DAAD17-03-C-0115 with the U.S. Army Research Laboratory. The views and conclusions contained in this document are those of the authors and should not be interpreted as presenting the official policies or position, either expressed or implied, of the U.S. Army Research Laboratory or the U.S. Government unless so designated by other authorized documents. Citation of trade names does not constitute an official endorsement or approval of the use thereof. The U.S. Government is authorized to reproduce and distribute reprints for Government purposes notwithstanding any copyright notation hereon.

REFERENCES

- Alemaný, M. M. G., Die'guez, O., Rey, C. and Gallego, L. J., 2001: A Density-Functional Study of the Structures and Electronic Properties of C₅₉Ni and C₆₀Ni Clusters, *J. Chem. Phys.*, **114**, 9371-9374.
- Büttiker, M., 1986: Four-Terminal Phase-Coherent Conductance, *Phys. Rev. Lett.*, **57**, 1761-1764.
- Datta, S., 1995: *Electronic Transport Properties in Mesoscopic Systems*, Cambridge University Press, Cambridge.
- Delley, B., 1990: An All-Electron Numerical Method for Solving the Local Density Functional for Polyatomic Molecules, *J. Chem. Phys.*, **92**, 508-517.
- Delley, B., 2000: From Molecules to Solids with the Dmol³ Approach, *J. Chem. Phys.*, **113**, 7756-7764.
- Frisch, M. J. *et al.*, 1998: GAUSSIAN03, Gaussian, Inc., Pittsburgh PA.
- Heurich, J., Cuevas, J. C., Wenzel, W. and Schön, G., 2002: Electrical transport through single-molecule junctions: from molecular orbitals to conduction channels, *Phys. Rev. Lett.*, **88**, 256803.
- He, H., Pandey, R., Pati, R. and Karna, S. P., 2006: Spin-polarized electron transport of a self-assembled organic monolayer on a Ni(111) substrate: An organic spin switch, *Phys. Rev. B*, **73**, 195311.
- Landauer, R., 1989: Conductance Determined by Transmission: Probes and Quantised Constriction Resistance, *J. Phys.: Condens. Matter*, **1**, 8099-8110.
- Pasupathy, A. N., Bialczak, R. C., Martinek, J., Grose, J. E., Donev, L. A. K., McEuen, P. L. and Ralph, D. C., 2004: The Kondo Effect in the Presence of Ferromagnetism, *Science*, **306**, 86-89.
- Pati, R., Senapati, L., Ajayan, P. M. and Nayak, S. K., 2003: First-principles calculations of spin-polarized electron transport in a molecular wire: Molecular spin valve, *Phys. Rev. B*, **68**, 100407.
- Petta, J. R., Slater, S. K. and Ralph, D. C., 2004: Spin-dependent transport in molecular tunnel junctions, *Phys. Rev. Lett.*, **93**, 136601.
- Rocha, A. R., García-Suárez, V. M., Bailey, S. W., Lambert, C. J., Ferrer, J. and Sanvito, S., 2005: Towards Molecular Spintronics, *Nature Mater.*, **4**, 335-339.
- Wei, Y., Xu, Y., Wang, J. and Guo, H., 2004: Spin-valve effect in a carbon atomic wire, *Phys. Rev. B*, **70**, 193406.
- Xiong, Z. H., Wu, D., Vardeny, Z. V. and Shi, J., 2004: Giant magnetoresistance in organic spin-valves, *Nature*, **427**, 821-824.
- Zwolak, M. and Di Ventra, M., 2002: DNA Spintronics, *Appl. Phys. Lett.*, **81**, 925-927.